3) DigiMoni Id
Any Id: Monitor any TG
Same Id: Monitor the same TG

4) Slot Hold
Off: Turn off the slot hold
On: Turn on the slot hold

Recommend to turn on slot hold when monitor double slot TS1 and TS2, when the signal is disappear in one slot, instead of switching to the other slot at once, the radio will hold on some seconds and wait for the audio drop.

c. Press Select to enter the sub menu and set up.

7.11.1 Response and Save a call in Digital Monitor Mode

During Digital Monitor, when receive a call with unmatched ID, press 〔*-〕 key, the screen will display "*Monitor Response Setup Successfully*", press [PTT] key will reponse to the call.

Press 〔#1〕 key, the radio will remind you choose a Zone, press △ / ▽ key to choose a Zone, press select key to save the new channel to the Zone.

7.12 Bluetooth function (Optional with installed Bluetooth)

1) BHT Switch
It will allow select "Bluetooth ON" or "Bluetooth OFF", select "Bluetooth ON" to turn on the bluetooth function.

2) BHT Match
It will allow select "Enter Match" or "Exit Match", select "Enter Match" to start the bluetooth pairing.

3) Device Name
It will show the bluetooth information and version.

4) MIC while BHT
When bluetooth function is on, the radio microphone is default off. This function will allow you turn on the radio microphone.

5) Speaker while BHT
When bluetooth function is on, the radio speaker is default off. This function will allow you turn on the radio speaker.

6) BHT MIC Gain
This function will allow you select different MIC gain level for bluetooth headset.

7) BHT SPK Gain
This function will allow you select different speaker gain level for bluetooth headset.